



## DECLARATION OF PERFORMANCE

002 CPR 15.06.2013

1-THE PRODUCT TYPE	Dry-pressed ceramic FLOOR TILES, with water absorption $0,5 \% < E_b \leq 3 \%$ ,
2- INTENDED USE(S)	For internal and external walls and floorings
3- NAME AND CONTACT ADDRESS OF THE MANUFACTURER , TEL. FAX. MAIL WEB	GRANİSER GRANİT SERAMİK A.Ş. OSB.Akhisar/Manisa/TURKEY +90 236 427 2605 +90 236 427 2555 <a href="mailto:info@graniser.com.tr">info@graniser.com.tr</a> <a href="http://www.graniser.com">www.graniser.com</a>
4- SYSTEM(S) OF ASSESSMENT AND VERIFICATION OF CONSTANCY OF PERFORMANCE (AVCP)	3 AND 4
5- NAME AND IDENTIFICATION NUMBER OF NOTIFIED LABORATORY ,AVCP SYSTEM DOCUMENT ISSUED AND DATE OF ISSUE	TURKISH STANDART INSTITUTION ,notified laboratory number 1783, performed type testing on determination of release of dangerous substances (lead and cadmium) under system 3 and issued test report no. 149783 on 22 <sup>nd</sup> of May 2013

### 6-PERFORMANS BEYANLARI

ESSENTIAL CHARACTERISTICS	PERFORMANCE	HARMONISED TECHNICAL SPECIFICATION
Reaction to fire	Class A1 <sub>FL</sub> /A1	TS EN 14411/2013 EN 14411/2012
Release of dangerous substance, for: - Cadmium - Lead	< 0,005 mg/dm <sup>2</sup> < 0,005 mg/dm <sup>2</sup>	
Breaking strength Thickness ≥ 7,5 mm Thickness < 7,5 mm	>1100 N > 700 N	
Flexural Tensile Strength Thickness ≥ 7,5 mm Thickness < 7,5 mm	> 30 N/mm <sup>2</sup>	
Thermal shock resistance	Pass	
Durability for: - internal use: - external use: freeze-thaw resistance	Pass Pass	

The performance of the product identified in point 1 is in conformity with the declared performances in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

A.Uğur UĞURLU  
General Manager

Manisa 15.06.2019